

<b>Products</b>	Aquilon RS alpha, Aquilon RS1, Aquilon RS2, Aquilon RS3, Aquilon RS4, Aquilon C, Aquilon C+
<b>Date</b>	November 11 <sup>th</sup> , 2021
<b>Version</b>	2.3.0

*The version (s) indicated here above has (have) been tested and validated by the QA Department.*

---

## Technical Notes:

---

### Changes:

- Added support for the Web RCS authentication password.

### Requirements

- Any Analog Way LivePremier™ live presentation switcher
- A 3-series or 4-series Crestron processor with Ethernet connection
- Any Crestron XPanel compliant display

### Required software versions

- LivePremier™ firmware            2.00.231 or above  
or  
LivePremier™ Simulator            1.2.7 or above
- SIMPL Windows                    4.11.06 or above
- VTPro-e                              6.2.00.03 or above
- Smart Graphics™                  2.15.04.00 or above
- Device database                    200.05.001.00 or above
- Crestron database                 201.00.004.00 or above
- Simlp+ cross compiler            1.3 or above

# PREVIOUS VERSIONS

<b>Products</b>	Aquilon RS alpha, Aquilon RS1, Aquilon RS2, Aquilon RS3, Aquilon RS4, Aquilon C, Aquilon C+
<b>Date</b>	July 19 <sup>th</sup> , 2021
<b>Version</b>	2.2.0

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### Changes:

- Fixed a bug related to main module parameters which were not working on 3 series version.

### Requirements

- Any Analog Way LivePremier™ live presentation switcher
- A 3-series or 4-series Crestron processor with Ethernet connection
- Any Crestron XPanel compliant display

### Required software versions

- LivePremier™ firmware            2.00.231 or above  
or  
LivePremier™ Simulator            1.2.7 or above
- SIMPL Windows                    4.11.06 or above
- VTPro-e                              6.2.00.03 or above
- Smart Graphics™                  2.15.04.00 or above
- Device database                    200.05.001.00 or above
- Crestron database                 201.00.004.00 or above
- Simlp+ cross compiler            1.3 or above

<b>Products</b>	Aquilon RS alpha, Aquilon RS1, Aquilon RS2, Aquilon RS3, Aquilon RS4, Aquilon C, Aquilon C+
<b>Date</b>	June 30 <sup>th</sup> , 2021
<b>Version</b>	2.1.0

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### Changes:

- Added support for preset and master preset offset, allowing to choose on a range the range of presets different from the first 100 proposed by default.
- Fixed a bug related to feedback during a transition (TAKE).
- Added workaround for wake on Lan on Crestron 4-series version only. The WOL is now externalized to a SIMPL module in 4-series versions.

### Requirements

- Any Analog Way LivePremier™ live presentation switcher
- A 3-series or 4-series Crestron processor with Ethernet connection
- Any Crestron XPanel compliant display

### Required software versions

- LivePremier™ firmware 2.00.231 or above  
or  
LivePremier™ Simulator 1.2.7 or above
- SIMPL Windows 4.11.06 or above
- VTPro-e 6.2.00.03 or above
- Smart Graphics™ 2.15.04.00 or above
- Device database 200.05.001.00 or above
- Crestron database 201.00.004.00 or above
- Simlp+ cross compiler 1.3 or above

<b>Products</b>	Aquilon RS alpha, Aquilon RS1, Aquilon RS2, Aquilon RS3, Aquilon RS4, Aquilon C, Aquilon C+
<b>Date</b>	March 22, 2021
<b>Version</b>	2.0.0

*The version (s) indicated here above has (have) been tested and validated by the QA Department.*

## Technical Notes:

---

### Changes:

- Added support for up to 64 widgets for each multiviewer
- Added support for layer control on auxiliary outputs
- Added support for built-in timers control
- Added support for layer presets recall
- Fixed a bug with audio routing
- Added support for new Crestron database (200.xxx.xxx)

### Requirements

Any Analog Way LivePremier™ live presentation switcher  
or

LivePremier™ Simulator

- A 3-series or 4-series Crestron processor with Ethernet connection
- Any Crestron XPanel compliant display

### Required software versions

- LivePremier™ firmware            2.00.231 or above  
or  
LivePremier™ Simulator            1.2.7 or above
- SIMPL Windows                    4.11.06 or above
- VTPro-e                              6.2.00.03 or above
- Smart Graphics™                  2.15.04.00 or above
- Device database                    200.05.001.00 or above
- Crestron database                 201.00.004.00 or above
- Simlp+ cross compiler            1.3 or above

<b>Products</b>	Aquilon RS1, Aquilon RS2, Aquilon RS3, Aquilon RS4, Aquilon C, Aquilon C+
<b>Date</b>	October 14, 2019
<b>Version</b>	1.0.0

The version (s) indicated here above has (have) been tested and validated by the QA Department.

---

## Technical Notes:

---

### Initial published release

- Recall Screen/Aux Presets or Master Presets
- Display live sources and still image sources with dynamic snapshots and properties
- Change the background of a Screen or the source displayed in a layer
- Change the source displayed by an Auxiliary output
- Transitioning the Preview content to the Program
- Configure multiviewer output(s) widget sources
- Recall multiviewer presets
- Route de-embedded audio channels or Dante input audio channels to video outputs
- Control device (reboot, shutdown, sleep or wake over LAN)

### Requirements

- Any Analog Way LivePremier™ live presentation switcher (Aquilon RS1, Aquilon RS2, Aquilon RS3, Aquilon RS4, Aquilon C and Aquilon C+)
- A 3-series Crestron processor with Ethernet connection
- Any Crestron XPanel compliant display

### Recommended software versions

- LivePremier™ firmware            1.00.40 or above
- SIMPL Windows                    4.11.06 or above
- VPro-e                                6.2.00.03 or above
- Smart Graphics™                 2.15.04.00 or above
- Device database                    107.00.001 or above
- Crestron database                 81.05.001.00 or above
- Simlp+ cross compiler            1.3 or above